DL-02 3 INCH PUCK LIGHT





CCT	2700-5000K
BEAM ANGLE	110°
SDCM	SDCM≥7
COLOR RENDERING INDEX	RA≥90
WATTAGE	4W EACH
INPUT VOLTAGE	24VDC
LUMENS	200LM EACH
DIMMING OPTION	DEPENDS ON DRIVER
DIMMING RANGE	DEPENDS ON DRIVER
LIFE SPAN	50000H
LIGHT SOURCE TYPE	LED
NUMBER OF LIGHT SOURCES	1 EACH
MOUNTING TYPE	SURFACE MOUNT
PRODUCT DIMENSIONS	D 3" x H 0.5"
MATERIAL	ALUMINUM, PC
COLOR	WHITE
SURFACE PROCESSES	PAINTING
NET WEIGHT (PIECE)	0.47KG
IP RATING	IP20











DESCRIPTION

The durable die-cast aluminum housing of this lighting fixture features an edge lit design with smooth light output. Its internal strong magnets facilitate easy installation on a metal plate, while the corrosion and heatresistant powder-coated finish ensures long-lasting durability. Operating at 24VDC with a power consumption of 4W, it is suitable for residential applications. Additionally, it is available in a range of color temperatures from 2700K to 5000K, and its precise optics maximize efficiency, providing up to 60 lumens per watt.





