

DL-06 RECESSED MOUNT LED DOWNLIGHT



SPECIFICATIONS

CCT	3000/4000/5000K
EFFICACY	85lm/w
SDCM	SDCM \geq 7
COLOR RENDERING INDEX	RA \geq 90
WATTAGE	6-50W
INPUT VOLTAGE	AC120-277V
LUMENS	85lm/w
DIMMING OPTION	0-10V
DIMMING RANGE	N/A
LIFE SPAN	50000H
LIGHT SOURCE TYPE	LED
NUMBER OF LIGHT SOURCES	1
MOUNTING TYPE	RECESSED
PRODUCT DIMENSIONS	4/6/8/10 inch
MATERIAL	ALUMINUM
COLOR	WHITE/SILVER
SURFACE PROCESSES	N/A
NET WEIGHT (PIECE)	N/A
IP RATING	N/A

DESCRIPTION

The CCT Switchable feature offers three temperature options: 3000K, 3500K, and 4000K, as well as 3500K, 4000K, and 5000K, with an additional choice of 3000K, 4000K, and 5000K. The power is switchable across different wattages, including 12W, 8W, and 6W, 30W, 23W, and 15W, and 50W, 42W, and 37W. The UL frame is universal for retrofit, remodel, and new construction applications. Optional emergency battery backup units are available for 120-277V. The fixture is IC type and has a lifetime of 50,000 hours with 70% lumen maintenance.



Working on a new project or remodeling an old one



New Construction



Emergency Backup Solution UL Approved

