EMERGENCY & SECURITY

ONESPACE LIGHTING SOLUTIONS

EL-02


OUTDOOR SECURITY LIGHT



SPECIFICATIONS

ССТ	27-50K
BEAM ANGLE	N/A
SDCM	N/A
COLOR RENDERING INDEX	RA≥80
WATTAGE	30W
INPUT VOLTAGE	120VAC
LUMENS	70lm/w
DIMMING OPTION	N/A
DIMMING RANGE	N/A
LIFE SPAN	50000H
LIGHT SOURCE TYPE	LED
NUMBER OF LIGHT SOURCES	1-3
MOUNTING TYPE	SURFACE
PRODUCT DIMENSIONS	SEE DIAGRAM
MATERIAL	ALUMINUM, PLASTIC
COLOR	WHITE/BLACK/BRONZE/SILVER
SURFACE PROCESSES	PAINTING
NET WEIGHT (PIECE)	N/A
IP RATING	IP65





DESCRIPTION

The durable aluminum housing of the aim-able single, two, and three-head light fixtures ensures excellent heat dissipation. These fixtures feature precise optics for maximum efficiency, providing up to 70lm/W. With a 120V/60Hz input, they are available in a color temperature range of 2700-5000K, and a single CCT (with a lens can make the CCT changeable). Additionally, they incorporate motion detection within 70 feet and built-in dusk-to-dawn photocell sensors. The timer options include one, five, or ten minutes, along with an override option for constant-on mode. With an IP65 weatherproof rating, these fixtures are reliable in any weather condition.



